

CYCLE RAIL

(PAS68:2007) V/3500[N1]/48/15:0.0/0.0
(PAS68:2007) V/3500[N1]/48/90:1.5/0.0

(PAS68:2007) V/7500[N2]/64/15:0.0/10.8
(PAS68:2007) V/7500[N2]/64/90:2.6/12.8

HEIGHT ABOVE GROUND OF 750MM



Eagle Automation have a range of PAS68:2007 rated products that support the street furniture scene. Our cycle hoop module is highly versatile and it can be used to create planters, railing systems and other similar products.

MODEL APT20CR

A zero penetration short height cycle hoop rated with the N1 3.5ton vehicle at 48kph. This product was extensively tested at 2 angles. Designed to complement existing street furniture. Shallow depth foundation of just 250mm. Available in a variety of heights (minimum 750mm above ground) . Available with gaps between 800mm and 1200mm. Suitable for securing bikes, scooters and motorcycles. Galvanised / painted finish.

MODEL APT40CR

A zero penetration cycle hoop rated with the N2 7.5ton vehicle at 64kph. This product was extensively tested at 2 angles. Designed to complement existing street furniture. Impact tested and approved at 7.5 tonne 40mph Shallow depth foundation of just 250mm. Height above ground 1000mm. Available with gaps between 800mm and 1200mm. Suitable for securing bikes, scooters and motorcycles. Galvanised / painted finish.

SPECIFICATIONS

- ▶ **Height above ground**
 - APT20CR - 750mm
 - APT40CR - 1050mm
- ▶ **Shallow foundation**
 - 2000mm x 2000mm x 250mm
- ▶ Supplied as a pair with integral connections
- ▶ No re-bar required

